

KOSH Energy

KOSH Energy Technologies Pvt Ltd (KETPL) is a leading manufacturer of Lithium Battery Systems across chemistries and applications.

Technical Data Sheet for 61.2V 24Ah battery for Agricultural Applications

Cell

Type	Nominal Voltage	Nominal Capacity	Nominal C-Rate	Maximum C-Rate
NMC - Cylindrical	3.6 V	4 Ah	C/3	3C

Battery

Voltage (V)	61.2
Capacity(Ah)	24
Max Voltage(V)	71.4
Min Voltage (V)	47.6
Max Continuous Current(A)	12
Size(mm)*	220x135x90
Weight**(Kgs)	5
BMS features	Over Charge Protection, Over Current Protection, Short Circuit Protection, Under Voltage Protection, Over Temperature Cut-off, Cell Balancing "Add to above" : Pre- Discharge Circuit, RS-485 communication with access to the following parameters: BMS Status, cell voltages, pack current, cell temperatures, MOSFET temperature, SOC, SOH, balancing status and cell DC resistance
Life***	2000 cycles or 3 years whichever is earlier

Caution: It is recommended that the battery is charged only by a CC-CV charger approved by KOSH Energy

* Dimensions are subject to variations as per chosen orientation, enclosure and BMS.

** Approximate weights may vary depending upon chosen orientation, enclosure and BMS.

*** Capacity at End-Of-Life will be 80% of Nominal capacity.

Disclaimer: This datasheet is a standard version of a pre-manufactured battery pack. Customization/Prototyping will change these mentioned parameters. This TDS is for informative purposes only and should not be used for any technical/commercial or legal claims.