KE-TDS-60880

KOSH Energy

KOSH Energy Technologies Pvt Ltd (KETPL) is a leading manufacturer of Lithium Battery Systems across chemistries and applications.

Technical Data Sheet for 60.8V 80Ah battery for stationary energy storage Applications

Cell

Type	Nominal Voltage	Nominal Capacity	Nominal C-Rate	Maximum C-Rate
LFP-Prismatic	3.2 V	100 Ah	C/5	3C

Battery

Voltage (V)	60.8
Capacity(Ah)	80
Max Voltage(V)	68.4
Min Voltage (V)	47.5
Max Continuous Current(A)	26.6
Size(mm)*	350x280x230
Weight**(Kgs)	38
BMS features	Over Charge Protection, Over Current Protection, Short Circuit Protection, Under Voltage Protection, Over Temperature Cut-off, Cell Balancing '"Add to above" : Pre- Discharge Circuit, RS-485 communication with access to the following parameters: BMS Status, cell voltages, pack current, cell temperatures, MOSFET temperature, SOC, SOH, balancing status and cell DC resistance
Life***	2000 cycles or 3 years whichever is earlier

Caution: It is recommended that the battery is charged only by a CC-CV charger approved by KOSH Energy

* Dimensions are subject to variations as per chosen orientation, enclosure and BMS.

**Approximate weights may vary depending upon chosen orientation, enclosure and BMS.

***Capacity at End-Of-Life will be 80% of Nominal capacity.

Disclaimer: This datasheet is a standard version of a pre-manufactured battery pack. Customization/Prototyping will change these mentioned parameters. This TDS is for informative purposes only and should not be used for any technical/commercial or legal claims.

KOSH Energy Technologies Pvt Ltd

info@kosh.energy
+918882183472

Plot No.1, Patel Estate, B/H Por GIDC, Industrial Area, Vadodara - 391 212, Gujarat, India.